

DOUBLE ELLIPSOID LIGHT BULB USING TOTAL INTERNAL REFLECTION

FIELD OF THE INVENTION

[0001] The present invention relates generally to light emitting devices, and more particularly to a total internal reflection light bulb.

SUMMARY OF THE INVENTION

[0002] The present invention provides a light bulb using total internal reflection to provide more efficient focused output. The body of the light bulb is arranged having walls extending in an elliptical contour from a central focal plane to opposite ends. A light source includes a light-emitting medium or filament that extends between oppositely extending electrodes and is positioned to axially extend across a central cavity of the body.

[0003] In a preferred embodiment, the light bulb includes a solid body portion having a central cavity. The central cavity includes rare earths or additives used to produce different colors according to the application. The outer walls of the solid body portion extend elliptically in opposite directions to provide total internal reflection. Light emitted from the light source reflects off the outer walls of the light bulb and is directed toward the focus of each elliptical half of the bulb.

[0004] Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood however that the detailed description and specific examples, while indicating a preferred embodiment of the invention, are intended for purposes of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

404200 "E34400

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

[0006] Figure 1 is a perspective view of the dual ellipsoid light bulb according to a first embodiment;

[0007] Figure 2 is a perspective view of the dual ellipsoid light bulb according to a second embodiment;

[0008] Figure 3 is a sectional side view of a dual ellipsoid light bulb along line III-III of Figure 1;

[0009] Figure 4 is a ray trace of the light bulb of the first embodiment;

[0010] Figure 5 illustrates a basic ellipse;

[0011] Figure 6 is a semi-ellipse illustrating a ray trace having total internal reflection according to the teachings of this invention;

[0012] Figure 7 is a side view of the dual ellipsoid light bulb according to a second embodiment; and

[0013] Figure 8 is a ray trace of the light bulb of the second embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0014] With initial reference to the view of Figure 1, the light bulb according to the preferred embodiment is illustrated and generally identified at reference 10. The light bulb 10 is defined by body 20 having walls 22 and includes a light source 12 disposed therein. The light source 12 is positioned between electrodes 14.

[0017] The geometrical relationships of the dual ellipsoid configuration will now be described in greater detail. The alignment of overlapping first and second semi-ellipsoid geometries 32, 34 is determined according to the coincidental of the associated focal point

"C" for each ellipsoid 32, 34. The resulting dual ellipsoidal geometry allows light emitted from light source 12 to reflect from a more refractive medium n_1 (e.g., glass) to a less refractive medium n_2 (e.g., air) at an angle greater than the critical angle described by Snell's law or $\frac{\sin \theta_1}{\sin \theta_2} = n_{21}$, thus achieving the emission of light rays 50 at each end 36, 38

by total internal reflection. The critical angle is the angle of incidence for which the angle of refraction is $\sin \theta_c = \frac{n_2}{n_1}$ where n_2 of air = 1; $\sin \theta_c = \frac{1}{n_1}$.

[0018] Because the geometrical configuration of walls 22 of body 20 provide total internal reflection, the walls 22 effectively operate as the reflector. Therefore, bulb 10 is the reflector and the use of an external reflector is not needed. This configuration increases efficiency by eliminating an efficiency loss associated with incorporating a secondary reflector.

[0019] The principles of operation are more readily understood with reference to Figure 5, which shows a basic ellipse according to the equation $(x/A)^2 + (y/B)^2 = 1$. The basic ellipse includes x and y axis intersecting at a point Φ . The y axis intersects the basic ellipse at points y1 and y2, and the x axis intersects the basic ellipse at points x1 and x2. A semi-major axis A extends between points Φ and x2. A semi-minor axis B extends between point Φ and y1. The basic ellipse provides focal points F1 and F2. A distance C extends between point Φ and F2. The following relationships further define the elliptical geometry where:

$$L = \sqrt{((2C)^2 + y^2)}$$

$$@x = C$$

$$y = B\sqrt{1 - (C/A)^2}$$

$$\beta = 90 - \gamma - \alpha$$

$$\gamma = \arctan(y/2C)$$

$$\alpha = \arctan(AG/(2y))$$

$$R_l = (2C / \tan \beta) - y$$

$$D_l = 2((2C / \tan \beta) - y)$$

[0020] In use, half of the basic ellipse shown in Figure 6 is truncated at one end through a plane extending through its focal point. With reference to Figure 6, one-half of a basic ellipse is shown with a truncated end in planar alignment with focal point F1. Further, a target 30, such as a fiber bundle or light pipe, is positioned at focal point F2 for the basic elliptical shape. The gaussian intensity distribution is shown at reference 44. From this basic shape and basic ellipse equation above, the diameter of the illuminated zone D_l can be determined according to the following equation, where D_{spot} , or the diameter of target 30, equals one-half D_l and AG is the arc gap or filament length. The

equation may be approximated by: $D_l = AG \sqrt{\frac{4}{(B/C)^2 - (B/A)^2} + 1}$, or more accurately

defined as: $D_l = 2 \left[\left(\frac{2C}{\tan \beta} \right) - y \right]$ where $\beta = 90 - \gamma - \alpha$; $\alpha = \tan^{-1}(AG/2y)$; $\gamma = \tan^{-1}(y/2C)$.

[0021] Turning now to Figure 4, a ray trace model illustrating the light 50 emitted from bulb 10 is shown. Opposite ends 36, 38 are oriented to allow light transfer devices such as fiber optic bundles or light pipes to be attached thereto.

[0025] The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.